

MODEL	A320	162,065lbs	D Check	\$1.2m
VARIANT	-200L GW	73,500kgs	Engine Overhaul	\$0.8-2.8m
BUILD PERIOD	1988-2009	CFM56	Aircraft Rating	C-- (88-95) B-- (96-09)

		A320-200L GW 73.5t CFM56																				
YEAR	CMV	320LC	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029
1988	7.24	MID	6.26	5.66	5.49	4.87	4.27	3.58	3.19	2.88	2.22	1.85	-	-	-	-	-	-	-	-	-	-
LOW	5.86	CON.	6.16	5.47	5.17	4.46	3.80	3.09	2.68	2.37	1.79	1.48	-	-	-	-	-	-	-	-	-	-
HIGH	8.54	%	86.4	78.2	75.8	67.3	59.0	49.4	44.0	39.8	30.6	25.6	-	-	-	-	-	-	-	-	-	-
L/R	109	L/R	99	95	98	90	83	71	66	65	55	47	-	-	-	-	-	-	-	-	-	-
LR/F	1.51	LR/F	1.59	1.68	1.78	1.85	1.94	1.98	2.07	2.25	2.48	2.54	-	-	-	-	-	-	-	-	-	-
		BEST	6.40	5.91	5.83	5.29	4.75	4.09	3.73	3.45	2.73	2.33	-	-	-	-	-	-	-	-	-	-
		CON.	6.30	5.71	5.49	4.84	4.23	3.53	3.14	2.84	2.21	1.83	-	-	-	-	-	-	-	-	-	-
		%	88.4	81.7	80.5	73.0	65.7	56.6	51.6	47.7	37.7	32.1	-	-	-	-	-	-	-	-	-	-
LR/H	137	L/R	106	103	106	98	91	78	73	72	60	52	-	-	-	-	-	-	-	-	-	-
LR/H	1.89	LR/F	1.70	1.81	1.93	2.01	2.12	2.18	2.28	2.48	2.72	2.80	-	-	-	-	-	-	-	-	-	-
		WRST	5.22	4.49	4.18	3.50	2.88	2.22	1.87	1.60	-	-	-	-	-	-	-	-	-	-	-	-
		CON.	5.14	4.34	3.94	3.21	2.56	1.92	1.57	1.32	-	-	-	-	-	-	-	-	-	-	-	-
		%	72.1	62.0	57.7	48.4	39.8	30.7	25.8	22.1	-	-	-	-	-	-	-	-	-	-	-	-
LR/L	89	L/R	96	91	92	84	76	64	59	58	-	-	-	-	-	-	-	-	-	-	-	-
LR/L	1.22	LR/F	1.84	1.61	1.68	1.73	1.79	1.80	1.86	2.00	-	-	-	-	-	-	-	-	-	-	-	-
1989	8.70	MID	7.55	6.87	6.68	5.95	5.25	4.44	3.96	3.59	3.22	2.73	2.24	-	-	-	-	-	-	-	-	-
LOW	7.05	CON.	7.43	6.63	6.29	5.45	4.67	3.83	3.34	2.96	2.60	2.15	1.71	-	-	-	-	-	-	-	-	-
HIGH	10.27	%	86.8	78.9	76.7	68.3	60.4	51.0	45.5	41.3	37.0	31.3	25.7	-	-	-	-	-	-	-	-	-
L/R	124	L/R	111	108	111	103	96	83	77	77	76	66	55	-	-	-	-	-	-	-	-	-
LR/F	1.43	LR/F	1.47	1.57	1.67	1.73	1.82	1.86	1.95	2.14	2.36	2.42	2.44	-	-	-	-	-	-	-	-	-
		BEST	7.73	7.17	7.09	6.45	5.84	5.07	4.63	4.29	3.95	3.42	2.87	-	-	-	-	-	-	-	-	-
		CON.	7.60	6.92	6.68	5.91	5.19	4.37	3.90	3.54	3.19	2.69	2.19	-	-	-	-	-	-	-	-	-
		%	88.8	82.4	81.4	74.1	67.1	58.2	53.2	49.3	45.4	39.2	33.0	-	-	-	-	-	-	-	-	-
LR/H	155	L/R	120	117	121	113	105	92	86	85	84	73	61	-	-	-	-	-	-	-	-	-
LR/H	1.78	LR/F	1.59	1.70	1.82	1.90	2.01	2.06	2.17	2.37	2.60	2.68	2.72	-	-	-	-	-	-	-	-	-
		WRST	6.30	5.45	5.09	4.29	3.56	2.79	2.35	2.02	1.68	-	-	-	-	-	-	-	-	-	-	-
		CON.	6.20	5.27	4.80	3.93	3.17	2.41	1.98	1.66	1.35	-	-	-	-	-	-	-	-	-	-	-
		%	72.4	62.7	58.5	49.3	40.9	32.0	27.0	23.2	19.2	-	-	-	-	-	-	-	-	-	-	-
LR/L	100	L/R	108	103	105	98	89	76	69	68	56	-	-	-	-	-	-	-	-	-	-	-
LR/L	1.15	LR/F	1.43	1.50	1.58	1.62	1.68	1.69	1.75	1.89	2.06	-	-	-	-	-	-	-	-	-	-	-
1990	10.17	MID	8.86	8.08	7.88	7.03	6.25	5.31	4.75	4.32	3.90	3.81	3.19	2.43	-	-	-	-	-	-	-	-
LOW	8.24	CON.	8.72	7.81	7.42	6.44	5.56	4.58	4.00	3.56	3.14	3.00	2.43	1.80	-	-	-	-	-	-	-	-
HIGH	12.00	%	87.1	79.5	77.5	69.2	61.5	52.2	46.7	42.5	38.3	37.5	31.4	23.9	-	-	-	-	-	-	-	-
L/R	137	L/R	121	118	123	115	107	93	88	88	88	88	74	57	-	-	-	-	-	-	-	-
LR/F	1.35	LR/F	1.37	1.47	1.56	1.63	1.72	1.76	1.84	2.03	2.25	2.31	2.33	2.35	-	-	-	-	-	-	-	-
		BEST	9.06	8.43	8.36	7.63	6.94	6.06	5.54	5.15	4.77	4.76	4.07	3.18	-	-	-	-	-	-	-	-
		CON.	8.91	8.15	7.88	6.99	6.17	5.23	4.67	4.24	3.85	3.75	3.10	2.36	-	-	-	-	-	-	-	-
		%	89.1	82.9	82.2	75.0	68.3	59.6	54.5	50.7	46.9	46.8	40.1	31.3	-	-	-	-	-	-	-	-
LR/H	171	L/R	132	129	135	127	119	104	98	98	97	98	83	64	-	-	-	-	-	-	-	-
LR/H	1.68	LR/F	1.49	1.60	1.71	1.80	1.91	1.96	2.07	2.26	2.50	2.57	2.62	2.66	-	-	-	-	-	-	-	-
		WRST	7.39	6.42	6.01	5.09	4.25	3.36	2.85	2.45	2.06	1.93	-	-	-	-	-	-	-	-	-	-
		CON.	7.28	6.20	5.67	4.66	3.78	2.90	2.40	2.02	1.66	1.52	-	-	-	-	-	-	-	-	-	-
		%	72.7	63.2	59.1	50.0	41.8	33.1	28.0	24.1	20.2	19.0	-	-	-	-	-	-	-	-	-	-
LR/L	111	L/R	113	116	117	107	99	85	79	77	76	76	-	-	-	-	-	-	-	-	-	-
LR/L	1.09	LR/F	1.33	1.40	1.48	1.52	1.58	1.60	1.65	1.79	1.96	1.98	-	-	-	-	-	-	-	-	-	-
1991	11.63	MID	10.16	9.30	9.09	8.14	7.26	6.20	5.56	5.06	4.59	4.50	4.35	3.38	2.55	-	-	-	-	-	-	-
LOW	9.42	CON.	10.00	8.99	8.57	7.45	6.46	5.35	4.68	4.17	3.70	3.54	3.31	2.51	1.85	-	-	-	-	-	-	-
HIGH	13.73	%	87.4	80.0	78.2	70.0	62.4	53.3	47.8	43.5	39.4	38.6	37.4	29.1	21.9	-	-	-	-	-	-	-
L/R	149	L/R	132	130	136	127	120	105	99	99	100	100	98	77	60	-	-	-	-	-	-	-
LR/F	1.28	LR/F	1.30	1.40	1.49	1.56	1.65	1.69	1.77	1.95	2.17	2.23	2.25	2.28	2.34	-	-	-	-	-	-	-
		BEST	10.39	9.71	9.64	8.82	8.06	7.07	6.48	6.03	5.60	5.60	5.54	4.42	3.45	-	-	-	-	-	-	-
		CON.	10.23	9.38	9.09	8.08	7.17	6.10	5.46	4.96	4.52	4.41	4.22	3.28	2.51	-	-	-	-	-	-	-
		%	89.3	83.4	82.9	75.9	69.3	60.8	55.7	51.8	48.1	48.1	47.7	38.0	29.6	-	-	-	-	-	-	-
LR/H	186	L/R	145	143	150	141	134	117	111	111	111	112	111	87	68	-	-	-	-	-	-	-
LR/H	1.60	LR/F	1.42	1.54	1.65	1.73	1.84	1.89	2.00	2.19	2.42	2.50	2.54	2.58	2.67	-	-	-	-	-	-	-
		WRST	8.49	7.40	6.95	5.89	4.96	3.95	3.35	2.89	2.45	2.30	2.12	-	-	-	-	-	-	-	-	-
		CON.	8.35	7.15	6.55	5.40	4.41	3.41	2.82	2.38	1.97	1.81	1.61	-	-	-	-	-	-	-	-	-
		%	73.0	63.6	59.7	50.7	42.6	33.9	28.8	24.8	21.0	19.8	18.2	-	-	-	-	-	-	-	-	-
LR/L	120	L/R	128	126	129	119	110	95	88	88	87	86	83	-	-	-	-	-	-	-	-	-
LR/L	1.04	LR/F	1.26	1.34	1.41	1.46	1.52	1.53	1.59	1.73	1.90	1.92	1.91	-	-	-	-	-	-	-	-	-
1992	13.10	MID	11.48	10.54	10.32	9.26	8.30	7.11	6.39	5.82	5.30	5.20	5.04	4.54	3.52	2.51	-	-	-	-	-	-
LOW	10.61	CON.	11.29	10.18	9.72	8.48	7.38	6.14	5.38	4.79	4.28	4.09	3.84	3.37	2.56	1.79	-	-	-	-		

		A320-200LW 73.5t CFM56																				
YEAR	CMV	320LC	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029
LR/L	1.07	LR/L	1.10	1.19	1.28	1.35	1.43	1.46	1.54	1.71	1.92	1.97	1.99	2.00	2.06	2.11	2.17	2.22	2.27	2.32	-	-
		BEST	17.18	16.27	16.35	15.13	14.03	12.50	11.55	10.84	10.21	10.26	10.24	9.53	8.91	7.90	7.75	7.01	5.36	4.21	-	-
		CON	16.91	15.72	15.41	13.86	12.48	10.79	9.73	8.92	8.24	8.08	7.80	7.07	6.48	5.63	5.42	4.80	3.56	2.71	-	-
		%	90.6	85.9	86.3	79.8	74.0	66.0	61.0	57.2	53.9	54.1	54.0	50.3	47.0	41.7	40.9	37.0	28.3	22.2	-	-
LR/H	253	LR/L	206	208	223	213	206	185	176	179	183	186	184	170	160	141	140	126	96	75	-	-
LR/H	1.33	LR/L	1.22	1.33	1.45	1.53	1.63	1.68	1.77	1.96	2.18	2.25	2.28	2.31	2.39	2.46	2.53	2.60	2.67	2.74	-	-
		WRST	14.04	12.43	11.81	10.15	8.72	7.10	6.08	5.30	4.60	4.35	4.05	3.46	2.91	2.27	2.04	1.66	-	-	-	-
		CON	13.82	12.01	11.13	9.30	7.75	6.13	5.12	4.36	3.71	3.42	3.09	2.57	2.12	1.61	1.43	1.13	-	-	-	-
		%	74.1	65.6	62.3	53.6	46.0	37.5	32.1	27.9	24.3	22.9	21.4	18.2	15.4	12.0	10.8	8.7	-	-	-	-
LR/L	164	LR/L	179	178	187	176	167	146	137	138	141	141	136	123	113	99	96	85	-	-	-	-
LR/L	86	LR/L	1.06	1.14	1.22	1.26	1.32	1.33	1.38	1.52	1.68	1.70	1.69	1.67	1.70	1.72	1.73	1.75	-	-	-	-
1997	20.42	MID	18.16	16.91	16.76	15.21	13.84	12.06	10.92	10.04	9.27	9.14	8.94	8.14	7.43	6.41	6.16	5.43	4.66	3.62	2.86	-
LOW	16.54	CON	17.87	16.34	16.79	13.93	12.30	10.41	9.19	8.26	7.48	7.20	6.81	6.04	5.41	4.56	4.30	3.71	3.10	2.33	1.79	-
HIGH	24.09	%	38.9	82.3	82.1	74.5	67.8	59.1	53.5	49.2	45.4	44.8	43.8	39.3	36.4	31.4	30.2	26.6	22.8	17.7	10.0	-
LR/L	214	LR/L	195	198	212	202	195	173	165	169	175	177	174	160	150	133	131	118	103	82	66	-
LR/L	1.05	LR/L	1.08	1.17	1.26	1.33	1.41	1.44	1.51	1.68	1.89	1.94	1.95	1.96	2.02	2.07	2.12	2.17	2.22	2.27	2.31	-
		BEST	18.57	17.64	17.77	16.48	15.33	13.70	12.68	11.91	11.25	11.32	11.31	10.55	9.89	8.80	8.64	7.83	6.92	5.55	4.53	-
		CON	18.28	17.04	16.75	15.10	13.63	11.82	10.68	9.81	9.08	8.92	8.61	7.83	7.20	6.26	6.04	5.36	4.59	3.56	2.83	-
		%	90.9	86.4	87.0	80.7	75.1	67.1	62.1	58.3	55.1	55.5	55.4	51.6	48.4	43.1	42.3	38.4	33.9	27.2	22.2	-
LR/H	267	LR/L	219	222	239	229	222	199	190	194	199	202	201	185	175	155	153	139	122	97	79	-
LR/H	1.31	LR/L	1.20	1.31	1.42	1.51	1.61	1.65	1.74	1.93	2.15	2.21	2.25	2.28	2.35	2.42	2.49	2.56	2.62	2.69	2.75	-
		WRST	15.18	13.48	12.84	11.06	9.53	7.79	6.69	5.84	5.08	4.81	4.50	3.85	3.26	2.56	2.32	1.89	1.51	-	-	-
		CON	14.94	13.02	12.10	10.13	8.48	6.73	5.63	4.81	4.10	3.79	3.42	2.86	2.37	1.82	1.62	1.29	1.01	-	-	-
		%	74.3	66.0	62.9	54.2	46.7	38.2	32.7	28.6	24.9	23.6	22.0	18.8	16.0	12.5	11.3	9.2	7.4	-	-	-
LR/L	173	LR/L	190	189	200	188	180	158	148	150	153	152	148	133	124	108	104	93	80	-	-	-
LR/L	85	LR/L	1.04	1.12	1.19	1.24	1.30	1.37	1.46	1.59	1.65	1.67	1.66	1.64	1.66	1.68	1.70	1.71	1.72	-	-	-
1998	21.88	MID	19.53	18.25	18.13	16.50	15.06	13.16	11.94	10.99	10.17	10.05	9.85	8.98	8.23	7.12	6.85	6.05	5.20	4.69	3.79	2.84
LOW	17.72	CON	17.72	17.63	18.09	15.11	13.36	10.95	9.65	8.21	7.01	6.75	6.66	5.99	5.07	4.79	4.14	3.30	3.01	2.36	1.72	
HIGH	25.82	%	89.8	83.4	82.7	72.5	64.6	60.5	54.5	50.2	45.5	45.9	47.0	41.0	37.6	32.5	31.4	27.3	21.4	13.3	13.0	
LR/L	224	LR/L	206	209	225	215	209	186	177	182	189	191	188	172	162	144	142	128	113	104	85	65
LR/L	1.02	LR/L	1.06	1.15	1.24	1.30	1.39	1.41	1.48	1.65	1.86	1.90	1.91	1.92	1.97	2.02	2.07	2.12	2.16	2.21	2.25	2.30
		BEST	19.97	19.03	19.23	17.88	16.68	14.94	13.86	13.04	12.34	12.44	12.45	11.63	10.94	9.75	9.60	8.71	7.70	7.15	5.96	4.63
		CON	19.66	18.38	18.12	16.38	14.83	12.90	11.67	10.74	9.96	9.80	9.48	8.63	7.96	6.94	6.71	5.96	5.11	4.59	3.72	2.81
		%	91.3	87.0	87.9	81.7	76.2	68.3	63.3	59.6	56.4	56.9	56.9	53.1	50.0	44.6	43.9	39.8	35.2	32.7	27.2	21.2
LR/H	280	LR/L	231	236	254	245	238	214	205	209	215	219	217	201	190	169	167	152	134	123	102	78
LR/H	1.28	LR/L	1.18	1.29	1.40	1.48	1.58	1.63	1.72	1.90	2.12	2.18	2.21	2.24	2.31	2.37	2.44	2.51	2.57	2.63	2.70	2.76
		WRST	16.32	14.55	13.90	12.01	10.38	8.52	7.32	6.40	5.60	5.31	4.97	4.26	3.63	2.87	2.61	2.13	1.71	1.38	-	-
		CON	16.07	14.05	13.10	11.00	9.23	7.35	6.17	5.27	4.52	4.18	3.78	3.16	2.64	2.04	1.82	1.46	1.14	0.89	-	-
		%	74.6	66.5	63.5	54.9	47.4	38.9	33.5	29.3	25.6	24.2	22.7	19.5	16.6	13.1	11.9	9.7	7.8	6.3	-	-
LR/L	182	LR/L	200	201	213	201	192	169	159	161	165	165	160	144	134	117	114	101	87	79	-	-
LR/L	83	LR/L	1.02	1.10	1.17	1.22	1.28	1.33	1.39	1.46	1.62	1.64	1.62	1.61	1.63	1.64	1.66	1.67	1.68	1.69	1.71	1.72
1999	23.35	MID	20.92	19.62	19.55	17.84	16.33	14.31	13.01	12.01	11.14	11.02	10.81	9.88	9.08	7.88	7.60	6.73	5.79	5.23	4.90	3.76
LOW	18.91	CON	20.59	18.95	18.42	16.34	14.52	12.35	10.95	9.88	8.99	8.62	8.23	7.68	6.58	5.81	4.60	3.84	3.28	3.06	2.28	
HIGH	27.55	%	89.6	84.0	83.7	76.9	69.9	61.3	55.7	51.4	47.7	47.2	46.3	42.3	38.9	33.7	32.6	28.8	24.8	22.4	16.1	
LR/L	234	LR/L	216	221	238	228	222	198	189	195	203	205	202	186	175	156	154	139	122	112	107	84
LR/L	1.00	LR/L	1.03	1.13	1.22	1.28	1.36	1.38	1.45	1.62	1.82	1.86	1.87	1.88	1.93	1.97	2.02	2.06	2.11	2.15	2.19	2.23
		BEST	21.39	20.46	20.73	19.33	18.08	16.25	15.10	14.24	13.51	13.64	13.67	12.79	12.05	10.78	10.62	9.66	8.54	7.95	7.67	6.08
		CON	21.05	19.76	19.53	17.70	16.08	14.02	12.72	11.72	10.90	10.74	10.41	9.49	8.77	7.67	7.42	6.60	5.67	5.11	4.79	3.69
		%	91.6	87.6	88.8	82.8	77.4	69.6	64.7	61.0	57.9	58.4	58.5	54.8	51.6	46.2	45.5	41.4	36.6	34.1	32.9	26.1
LR/H	293	LR/L	243	249	270	260	254	229	219	224	232	236	235	217	205	183	182	165	146	135	129	101
LR/H	1.25	LR/L	1.16	1.27	1.38	1.46	1.56	1.60	1.69	1.87	2.08	2.14	2.17	2.20	2.26	2.33	2.39	2.45	2.52	2.58	2.64	2.69
		WRST	17.49	15.64	14.99	12.99	11.26	9.27	7.99	7.00	6.14	5.83	5.47	4.70	4.03	3.20	2.92	2.40	1.93	1.57	1.32	-
		CON	17.21	15.11	14.12	11.89	10.01	8.00	6.73	5.76	4.96	4.59	4.16	3.49	2.93	2.28	2.04	1.64	1.28	1.01	0.83	-
		%	74.9	67.0	64.2	55.6	48.2	39.7	34.2	30.0	26.3	25.0	23.4	20.1	17.3	13.7	12.5	10.3	8.3</			

A320-200LW 73.5t CFM56																						
YEAR	CMV	320LC	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029
LOW	26.03	CON.	28.76	28.96	26.77	24.32	22.12	19.23	17.35	15.90	14.71	14.37	13.81	12.46	11.41	9.85	9.43	8.26	6.95	6.17	5.71	5.00
HIGH	37.91	%	90.9	86.9	88.4	82.6	77.4	69.3	64.1	60.1	56.7	58.8	56.4	52.2	48.8	43.0	42.0	37.6	32.6	29.9	28.5	25.7
LR	281	L/R	264	275	304	300	298	268	257	269	287	291	287	264	250	224	222	201	177	164	158	144
LR/H	88	LR/F	90	99	1.07	1.13	1.20	1.20	1.25	1.39	1.58	1.60	1.59	1.57	1.60	1.62	1.64	1.67	1.69	1.71	1.73	1.75
LRFF																						
		BEST	29.88	29.11	30.11	28.77	27.53	25.27	23.89	22.88	22.06	22.54	22.87	21.66	20.72	18.80	18.72	17.20	15.32	14.45	14.11	13.10
		CON.	29.41	28.11	28.38	26.34	24.48	21.82	20.12	18.83	17.80	17.75	17.42	16.08	15.08	13.38	13.08	11.76	10.17	9.28	8.80	7.93
		%	93.0	90.6	93.7	89.5	85.7	78.7	74.4	71.2	68.7	70.2	71.2	67.4	64.5	58.5	58.3	53.5	47.7	45.0	43.9	40.8
LR/H	352	L/R	303	317	352	349	349	317	307	318	336	344	343	318	304	274	273	250	221	206	200	184
LRFF	1.09	LR/F	1.04	1.14	1.24	1.31	1.40	1.42	1.49	1.65	1.85	1.88	1.89	1.90	1.94	1.98	2.03	2.07	2.11	2.15	2.19	2.23
		WRST	24.43	22.27	21.80	19.36	17.21	14.51	12.72	11.33	10.13	9.74	9.26	8.09	7.11	5.81	5.39	4.51	3.65	3.10	2.73	2.24
		CON.	24.05	21.51	20.54	17.73	15.30	12.52	10.71	9.32	8.18	7.67	7.05	6.01	5.17	4.14	3.77	3.08	2.42	1.99	1.70	1.36
		%	76.0	69.3	67.8	60.2	53.6	45.2	39.6	35.2	31.5	30.3	28.8	25.2	22.1	18.1	16.8	14.0	11.4	9.6	8.5	7.0
LR/L	228	L/R	256	264	288	280	276	243	231	238	251	251	244	221	206	182	178	159	137	125	119	107
LRFL	71	LR/F	88	94	1.01	1.05	1.11	1.09	1.12	1.23	1.38	1.38	1.35	1.31	1.32	1.32	1.32	1.31	1.31	1.31	1.31	1.29
2006	33.60	MID	30.56	29.20	29.71	27.78	26.16	23.55	21.86	20.56	19.47	19.55	19.48	18.08	16.93	14.98	14.65	13.13	11.40	10.49	10.02	9.05
LOW	27.21	CON.	30.08	28.20	28.00	25.44	23.26	20.33	18.41	16.93	15.71	15.40	14.83	13.42	12.32	10.66	10.24	8.98	7.57	6.74	6.25	5.48
HIGH	39.64	%	91.0	86.9	88.4	82.7	77.9	70.1	65.1	61.2	58.0	58.2	58.0	53.8	50.4	44.6	43.6	39.1	33.9	31.2	29.8	26.9
LR	287	L/R	269	281	310	306	306	274	264	277	297	301	297	272	258	231	229	208	182	169	163	149
LRFF	85	LR/F	88	96	1.04	1.10	1.17	1.16	1.21	1.35	1.53	1.54	1.52	1.51	1.53	1.54	1.56	1.58	1.60	1.62	1.63	1.65
		BEST	31.24	30.44	31.50	30.09	28.96	26.71	25.35	24.36	23.57	24.15	24.57	23.33	22.37	20.35	20.30	18.69	16.67	15.75	15.42	14.34
		CON.	30.75	29.41	29.68	27.56	25.75	23.05	21.35	20.05	19.02	19.02	18.71	17.31	16.28	14.49	14.19	12.78	11.07	10.12	9.62	8.68
		%	93.0	90.6	93.8	89.6	86.2	79.5	75.4	72.5	70.1	71.9	73.1	69.4	66.6	60.6	60.4	55.6	49.6	46.9	45.9	42.7
LR/H	359	L/R	310	325	360	357	359	327	317	330	349	358	357	331	317	286	285	261	230	216	210	193
LRFF	1.07	LR/F	1.01	1.11	1.21	1.29	1.37	1.39	1.45	1.60	1.80	1.83	1.83	1.87	1.91	1.95	1.98	2.02	2.06	2.09	2.13	
		WRST	25.55	23.30	22.81	20.25	18.10	15.34	13.50	12.07	10.83	10.44	9.96	8.73	7.69	6.32	5.87	4.92	3.99	3.40	3.02	2.49
		CON.	25.15	22.50	21.49	18.55	16.10	13.24	11.37	9.93	8.74	8.22	7.58	6.48	5.60	4.50	4.10	3.37	2.65	2.19	1.88	1.51
		%	76.1	69.3	67.9	60.3	53.9	45.7	40.2	35.9	32.2	31.1	29.6	26.0	22.9	18.8	17.5	14.7	11.9	10.1	9.0	7.4
LR/L	233	L/R	261	269	293	285	282	249	237	245	259	259	252	228	213	188	183	164	141	129	123	110
LRFL	69	LR/F	85	92	99	1.03	1.08	1.08	1.08	1.19	1.33	1.33	1.29	1.26	1.26	1.25	1.25	1.24	1.24	1.23	1.23	1.22
2007	35.06	MID	31.89	30.48	31.02	29.01	27.48	24.87	23.19	21.90	20.82	20.97	20.95	19.50	18.32	16.25	15.93	14.31	12.44	11.47	10.98	9.95
LOW	28.40	CON.	31.39	29.44	29.23	26.56	24.44	21.47	19.53	18.03	16.80	16.51	15.95	14.47	13.33	11.57	11.13	9.78	8.26	7.37	6.85	6.03
HIGH	41.37	%	91.0	86.9	88.5	82.7	78.4	70.9	66.1	62.5	59.4	59.8	59.8	55.6	52.2	46.3	45.4	40.8	35.5	32.7	31.3	28.4
LR	292	L/R	274	285	315	310	312	280	270	284	306	310	305	279	265	237	235	213	187	173	167	153
LRFF	83	LR/F	86	94	1.02	1.07	1.13	1.13	1.16	1.30	1.47	1.48	1.46	1.43	1.45	1.46	1.47	1.49	1.50	1.51	1.52	1.54
		BEST	32.61	31.78	32.88	31.42	30.41	28.20	26.89	25.94	25.19	25.10	26.42	25.16	24.19	22.06	22.06	20.34	18.18	17.21	16.88	15.73
		CON.	32.10	30.70	30.99	28.77	27.04	24.34	22.64	21.36	20.33	20.39	20.12	18.67	17.60	15.11	15.42	13.91	12.07	11.06	10.53	9.53
		%	93.0	90.6	93.8	89.6	86.7	80.4	76.7	74.0	71.9	73.9	75.4	71.8	69.0	62.9	62.9	58.0	51.9	49.1	48.1	44.9
LR/H	365	L/R	316	331	367	364	368	335	326	340	362	371	370	344	329	297	296	271	239	224	218	201
LRFF	1.04	LR/F	99	1.09	1.18	1.26	1.34	1.35	1.40	1.55	1.74	1.77	1.77	1.76	1.80	1.83	1.86	1.89	1.93	1.96	1.99	2.02
		WRST	26.67	24.32	23.81	21.15	19.02	16.21	14.33	12.86	11.59	11.21	10.72	9.43	8.34	6.88	6.41	5.39	4.38	3.75	3.34	2.77
		CON.	26.25	23.49	22.44	19.37	16.91	13.99	12.07	10.59	9.36	8.83	8.16	7.00	6.07	4.90	4.48	3.68	2.90	2.41	2.08	1.68
		%	76.1	69.4	67.9	60.3	54.2	46.2	40.9	36.7	33.1	32.0	30.6	26.9	23.8	19.6	18.3	15.4	12.5	10.7	9.5	7.9
LR/L	237	L/R	265	273	298	290	287	254	242	251	267	267	259	234	219	193	188	168	145	133	126	113
LRFL	68	LR/F	83	90	96	1.00	1.05	1.02	1.04	1.15	1.28	1.27	1.24	1.20	1.19	1.19	1.19	1.17	1.16	1.15	1.15	1.14
2008	36.52	MID	33.23	31.76	32.33	30.23	28.84	26.25	24.61	23.34	22.28	22.53	22.58	21.07	19.86	17.67	17.36	15.64	13.61	12.59	12.08	10.97
LOW	29.58	CON.	32.71	30.68	30.46	27.68	25.64	22.66	20.72	19.22	17.98	17.74	17.19	15.64	14.45	12.58	12.13	10.69	9.04	8.09	7.54	6.64
HIGH	43.10	%	91.0	87.0	88.5	82.8	78.9	71.9	67.4	63.9	61.0	61.7	61.8	57.7	54.4	48.4	47.5	42.8	37.3	34.5	33.1	30.0
LR	297	L/R	277	288	318	313	317	284	274	289	313	318	318	285	270	242	239	216	189	176	170	155
LRFF	81	LR/F	83	91	99	1.04	1.10	1.08	1.11	1.24	1.41	1.41	1.38	1.35	1.36	1.37	1.38	1.38	1.39	1.40	1.40	1.41
		BEST	33.98	33.12	34.27	32.74	31.91	29.77	28.53	27.65	26.96	27.82	28.47	27.19	26.22	23.98	24.04	22.21	19.88	18.87	18.54	17.31
		CON.	33.44	31.99	32.29	29.99	28.37	25.70	24.02	22.76	21.76	21.90	21.68	20.18	19.08	17.07	16.79	15.19	13.20	12.12	11.57	10.49
		%	93.0	90.7	93.8	89.7	87.4	81.5	78.1	75.7	73.8											